

LFC3-LD

True Hydrophilic Membrane Chemistry with LD Technology™

LFC3-LD from the LD Technology™ innovative low fouling membranes combines the attributes of a neutrally charged surface with hydrophilicity to achieve the lowest colloidal fouling in the most demanding feed water conditions

Superior membrane technology is the key to Hydranautics' innovative LFC (Low Fouling Composite) membranes. LFC3-LD membranes offer breakthrough technology in the treatment of difficult feedwaters and municipal wastewaters. Until now, these applications required significant pretreatment prior to being subjected to a composite polyamide membrane, which is eliminated with the use of the LFC3-LD membrane.

Combining the attributes of a neutral surface charge and hydrophilicity, LFC3-LD provides significant reduction in fouling rates increasing the membrane's efficiency by restoring nominal performance after cleaning.

The low fouling composite LFC3-LD (Low Differential Pressure) provides a neutral surface charge that reduces fouling when treating wastewater and surface water with high fouling potential. With the low fouling LD Technology™, the differential pressure gets reduced lowering the colloidal fouling inside the membrane, and successfully reducing the number of cleanings required!

Key benefits:

- High permeate flow - 11,000 gpd (41.6 m³/d)
- High salt rejection - 99.7% (99.5% minimum)
- Increased membrane durability
- Lower dP (differential pressure)
- Greater tolerance to high pH cleanings
- Improved flux distribution

Applications:

- Municipal wastewater treatment
- Industrial wastewater treatment
- Wastewater with high biological and organic fouling potential

Performance:

Permeate Flow	11,000 gpd (41.6 m³/d)
Salt Rejection	99.7% (99.5 % minimum)

Applications Data:

pH Range, Continuous (Cleaning)	2-10 (1-12)*
Maximum Feedwater SDI (15 min)	5.0
Maximum Feed Flow	75 GPM (17.0 m³/h)

* The limitations shown here are for general use. For specific projects, operating at more conservative values may ensure the best performance and longest life of the membrane. See Hydranautics Technical Bulletins for more detail on operation limits, cleaning pH, and cleaning temperatures.

Test Conditions:

The stated performance is initial (data taken after 30 minutes of operation), based on the following conditions

1500 PPM NaCl solution
225 psi (1.55 MPa) Applied Pressure
77°F (25° C) Operating Temperature
15% Permeate Recovery
6.5 - 7.0 pH Range



Features:

- **Enhanced membrane chemistry** for increased chemical resistance
- **Innovative spacer design** to minimize trapping of small colloidal particles
- **Proprietary vented seal carrier** to eliminate pressure-shock damage during system startup.

LFC3-LD, Low Fouling Composite Polyamide RO Membranes, for Your Water Treatment Needs!



Hydranautics - A Nitto Group Company is a global leader in research, including reverse osmosis, nanofiltration, ultrafiltration, and microfiltration. Our membrane products (CPA, ESPA, LFC, SWC, ESNA, HYDRAcap and HYDRAsub) are used extensively in municipal & industrial water and wastewater treatment.

Hydranautics has over 40 years experience in the membrane technology arena and are committed to creating innovative membrane technologies which provide clean water to a thirsty world.

Our global membrane division is headquartered in Oceanside, CA, USA. With three state-of-the-art manufacturing sites located in Oceanside - CA - USA, Shiga - Japan and Shanghai – China, Hydranautics has a combined manufacturing area in excess of 131,000 m² (1,400,000 ft²). Our world-wide sales and customer service offices are located throughout Europe, Asia, the Middle East, North America and South America.

Solutions You Need.

Technologies You Trust!

Hydranautics Corporate Office:

401 Jones Road, Oceanside, CA 92058, USA . Toll Free: 1-800-CPA-PURE Phone: +760-901-2500 Fax: +760-901-2578
Email: info@hydranautics.com Website: www.membranes.com

Americas Hydranautics

401 Jones Road
Oceanside, CA
92058, USA
Tel: +760-901-2500
Tel: 1-800-CPAPURE
Fax: +760-901-2578

Europe/Africa Hydranautics

Calle Constitucion 3,
3° 5ª Sant Just Desvern,
08960 Barcelona
Spain
Tel: +34 934 731 722
Fax: +34 934 731 485

Middle East Hydranautics

Office no 31
Bldg no . S10122 (A2)
South Zone,
Jebel Ali Free Zone
P.O.Box: 112839 Dubai
United Arab Emirates
Tel: +971 4 889 5806

Indian Subcontinent Hydranautics

407, Palm Springs
Center, Link Road,
Malad (West),
Mumbai 400 064,
India
Tel: +91-22-40030500
Fax: +91-22-40030496

S.E. Asia/Australia Nitto

438 Alexandra Road
#19-01/04,
Alexandra Point
Singapore 119958
Tel: +65-6879-3820
Fax: +65-6223-7690

Japan Hydranautics / Nitto

26F, Shinagawa Season Terrace,
1-2-70, Konan,
Minato-ku, 108-0075,
Tokyo
Tel: +81-3-6632-2044
Fax: +81-3-6632-2019