



Disposal of Used RO Elements

October 2013 TSB123.02

The following provides general information on how to dispose of used RO elements.

Disposal

Users are responsible for ensuring that elements are disposed of in accordance with all local and federal regulations in the applicable jurisdiction. Used elements typically can be disposed of as municipal waste provided that they do not contain any free liquids or hazardous substances at levels that exceed regulatory thresholds. If the user wishes to pursue recycling options for waste elements, information regarding the composition of unused reverse osmosis elements can be found in the table below.

Hydranautics – Reverse Osmosis Elements		
Element Component Weights		
Material	Weight (kg)	Weight (lbs.)
Polysulfone	.88	1.94
Polyester	5.59	12.34
Polypropylene	1.58	3.51
Polyurethane (2 Part)	2.17	4.79
Epoxy (2 Part)	.75	1.65
“E” Glass Roving	1.28	2.82
ABS (A <u>cr</u> ylonitrile-B <u>u</u> tadiene-S <u>t</u> yrene)	1.15	2.5
Polyamide	.05	.11
Noryl (Polyphenylene Ether)	.04	0.1
EPR (Ethylene Propylene Rubber)	.032	.075
Heavy Metals	~	~

For further information on the installation and care of Hydranautics products, contact your Sales Representative or the Technical Support department at Hydranautics.

Hydranautics

401 Jones Rd.

Oceanside, CA 92058

Tel: (760) 901-2500 Fax: (760) 901-2578

e:mail: info@hydranautics.com

Internet: www.membranes.com