



## **CPA7 Series**

#### **High Flow, High Rejection RO membranes**

The CPA7 series are the newest CPA brackish water RO membranes offering the highest salt rejection in the industry. These ultra-high rejection RO membranes are meant to fulfil your purest water quality requirements.

Where ultra-high purity water is required under difficult water conditions, the CPA7 membranes supply the best combination of high rejection and high flow capability in a brackish water RO element, compared to all commercial brackish water RO elements.

CPA7 membranes are useful in industries where highpurity water is critical like power generation, electronics, semiconductor, pharmaceutical and food & beverage.

The LD variant of these membranes using LD Technology® are available in 4" (CPA7-LD-4040) and 8" (CPA7-LD) diameters. The CPA7 MAX membrane has 440 ft² (40.9 m²) active membrane surface area which reduces capital costs by requiring fewer pressure vessels and lesser floor space.

#### **Key Features of CPA7 membranes**

- High rejection of TOC, boron, silica and nitrate
- Greater tolerance to high pH cleanings
- Lower energy consumption
- Best combination of high rejection/ low energy in the membrane industry

#### **CPA7** Features and benefits:

- Enhanced membrane chemistry for best permeate quality at lower feed pressure
- Improved chemical resistance for increased membrane
- Innovative feed spacer design to reduce cleaning frequency and costs

#### **CPA7 Applications:**

- Boiler makeup water for power generation
- Industrial waste water recovery
- Zero Liquid Discharge (ZLD) / HERO process
- Ultrapure water for semiconductor manufacturing
- Ultrapure water for pharmaceutical industries



#### **Specified Performance\* and General Product Description:**

	Model	Permeate flow* gpd (m³/d)	Salt Rejection* (nominal)	Feed Spacer Thickness (mil)	Membrane Active Area ft <sup>2</sup> (m <sup>2</sup> )
CPA7 series	CPA7-LD-4040	2,300 (8.7)	99.8%	34	80 (7.4)
	CPA7-LD	11,500 (43.5)	99.8%	34	400 (37.2)
	CPA7 MAX	12,600 (47.7)	99.8%	26-28	440 (40.9)

<sup>\*</sup> Test condition: 1500 ppm NaCl solution,1.55 MPa (225 psi) applied pressure, 15% recovery, operating temperature 25 °C. The Specified Performance is based on data taken after approximately 30 minutes of operation. Actual testing of elements may be done at conditions which vary from these exact values; in which case, the performance is normalized back to these standard conditions. Permeate flow for individual elements may vary ±15 percent from the value specified.

# **CPA7 series,** Composite Polyamide RO membranes, for High Purity Water Production!



thirsty world.

Our Global Membrane Division is headquartered in Oceanside, CA, USA. With three state-of-the-art manufacturing sites located in Oceanside – CA – USA, Shiga – Japan and Shanghai – China, Hydranautics has a combined manufacturing area in excess of 1,400,000 ft² (130,064 m²). Our world-wide sales and customer service offices are located throughout Europe, Asia, the Middle East, North America and South America.

### **Solutions You Need.**

## **Technologies You Trust!**

#### **Hydranautics Corporate office**

401 Jones Road, Oceanside, CA 92058, USA Toll Free: +1-800-CPA-PURE Tel: +1 760 901 2500 Fax: +1 760 901 2578 Web: www.membranes.com Email: hy-info@nitto.com

Americas 401 Jones Road, Oceanside, CA 92058, USA Tel: +1 760 901 2500 Europe and Africa
Calle Constitucion 3,
3° 5ª Sant Just
Desvern,
08960 Barcelona,
Spain
Tel: +34 934 731 722

Middle East
Office no. 31, Bldg no .
S10122 (A2) South Zone,
Jebel Ali Free Zone,
P.O.Box 112839
Dubai, UAE
Tel: +971 4 889 5806

Indian Subcontinent 407, Palm Spring Center, Link Road, Malad (West), Mumbai 400064, India Tel: +91 22 4003 0500 China 15-16F, The Place Tower C, 150 Zunyi Road, Changning District, Shanghai 200051, P.R. China

Tel: +86 21 5208 2255

SEA & Oceania 438 Alexandra Road #19-01/04, Alexandra Point, Singapore 119958 Tel: +65 6879 3820 Japan 26F, Shinagawa Season Terrace, 1-2-70, Konan, Minato-ku, 108-0075, Tokyo, Japan Tel: +81 3 6632 2044