

NANO-SW

Nanofiltration Membrane Technology for Sulfate Removal Process in Oil and Gas Industry

When high rejection of sulphate is required under demanding conditions, the NANO-SW membrane from Hydranautics sets new standards for high sulphate rejection.

Everyday new advancements are made in offshore oil drilling technology to keep pace with the rapid increase in global demand for oil. But the operation of an offshore oil well entails a significant investment because of the logistical and operational challenges involved. If the oil well were to face frequent downtime on account of inefficient processes, it would have a significant negative impact on the entire operation, increasing the costs.

This situation arises when sea water injection is used in offshore oil wells. The presence of sulphate in the sea water leads to problems like scale formation and reservoir souring.

The NANO-SW offers the perfect solution for this problem. It is a significantly robust membrane offering a high rejection of sulfate at 99.8%. This translates into fewer number of cleanings and reduced downtime for the oil well's operation.

Seawater injection in offshore oil well: In offshore oil production, seawater is injected into the oil reservoir, increasing the pressure and thereby stimulating and increasing the oil production.

The water injection technique: The sulfate content in seawater is usually 2500 ppm to 3000 ppm SO_4 . This can lead to scale formation and/or reservoir souring in the following manner.

Scale Formation:

Sulfate in seawater

+

Barium and strontium in reservoir formation

=

$BaSO_4$ and $SrSO_4$ scaling

Reservoir Souring:

Sweet reservoirs initially void of sulfate

+

Conversion of seawater sulfate in hydrogen sulphide gas by sulphate reducing bacteria (SRBs)

=

Reservoir souring

Key features:

- ⦿ High sulfate rejection – 99.8%
- ⦿ Superior selective membrane chemistry
- ⦿ Maximal flow
- ⦿ Low-fouling feed spacer design

Features and benefits:

- ⦿ **High sulfate rejection** prevents scale formation when the permeate mixes with groundwater containing barium
- ⦿ **High sodium and chloride passage** minimizes the increase in osmotic pressure leading to lower pressures
- ⦿ **Innovative feed spacer design** prevents trapping of colloidal particles and reduces the colloidal fouling of the NF membranes
- ⦿ **Lower fouling and easy cleanability** ensures that the membrane provides optimal and consistent performance throughout the membrane's life



Performance:

MgSO ₄	
Permeate Flow (Nominal)	11,000 gpd (41.6 m ³ /d)
MgSO ₄ Rejection	99.8% (99.6% minimum)
Seawater	
Permeate Flow* (Nominal)	6,500 gpd (24.6 m ³ /d)
Cl Rejection* (Nominal)	25%
SO ₄ Rejection (Nominal)	99.8%

*All elements are tested with MgSO₄ in Hydranautics' wet test QC. Seawater performance is for reference purposes.

Test Conditions:

MgSO₄

- ☉ 2000 ppm MgSO₄
- ☉ 130 psi (0.9 MPa) Applied Pressure
- ☉ 77 °F (25 °C) Operating Temperature
- ☉ 15% Permeate Recovery
- ☉ 6.5–7.0 pH Range

Seawater

- ☉ 35,000 ppm NaCl + 8000 ppm MgSO₄
- ☉ 200 psi (1.4 MPa) Applied Pressure
- ☉ 77 °F (25 °C) Operating Temperature
- ☉ 15% Permeate Recovery
- ☉ 6.5–7.0 pH Range

NANO-SW, High Sulphate Rejection Composite Polyamide NF membranes, for Your Water Treatment Needs!



Hydranautics – A Nitto Group Company is a global leader in research, including reverse osmosis, nanofiltration, ultrafiltration, and microfiltration. Our membrane products (CPA, ESPA, LFC, SWC, ESNA, HYDRAcapMAX and HYDRASub) are used extensively in municipal & industrial water and wastewater treatment.

Hydranautics has over 40 years experience in the membrane technology arena and are committed to creating innovative membrane technologies which provide clean water to a thirsty world.

Our Global Membrane Division is headquartered in Oceanside, CA, USA. With three state-of-the-art manufacturing sites located in Oceanside – CA – USA, Shiga – Japan and Shanghai – China, Hydranautics has a combined manufacturing area in excess of 1,400,000 ft² (130,064 m²). Our world-wide sales and customer service offices are located throughout Europe, Asia, the Middle East, North America and South America.

Solutions You Need.

Technologies You Trust!

Hydranautics Corporate office

401 Jones Road, Oceanside, CA 92058, USA Toll Free: +1-800-CPA-PURE Tel: +1 760 901 2500 Fax: +1 760 901 2578
Web: www.membranes.com Email: hy-info@nitto.com

Americas

401 Jones Road,
Oceanside,
CA 92058, USA
Tel: +1 760 901 2500

Europe and Africa

Calle Constitucion 3,
3° 5° Sant Just
Desvern,
08960 Barcelona,
Spain
Tel: +34 934 731 722

Middle East

Office no. 31, Bldg no .
S10122 (A2) South Zone,
Jebel Ali Free Zone,
P.O.Box 112839
Dubai, UAE
Tel: +971 4 889 5806

Indian Subcontinent

407, Palm Spring
Center, Link Road,
Malad (West),
Mumbai 400064,
India
Tel: +91 22 4003 0500

China

15-16F, The Place Tower
C, 150 Zunyi Road,
Changning District,
Shanghai 200051,
P.R. China
Tel: +86 21 5208 2255

SEA & Oceania

438 Alexandra Road
#19-01/04,
Alexandra Point,
Singapore 119958
Tel: +65 6879 3820

Japan

26F, Shinagawa
Season Terrace,
1-2-70, Konan,
Minato-ku, 108-0075,
Tokyo, Japan
Tel: +81 3 6632 2044